

45W, AC-DC converter



FEATURES

- Universal 85-264VAC or 100-370VDC input voltage
- High power density, compact size: 3" x 2" x 1.03"
- Operating ambient temperature range: -40°C to +70°C
- High I/O isolation test voltage up to 4000VAC
- Meets 5000m altitude requirements
- Extremely low leakage current <75uA
- Stand-by power consumption <0.3W
- Output short circuit, over-current, over-voltage protection
- Efficiency up to 90%
- Meets 2 x MOPP safety certification
- Suitable for BF application
- Over-voltage class III (designed to meet EN61558)
- Safety according to IEC/EN/ES60601-1, UL/EN/IEC62368-1, IEC/EN60335-1, IEC/EN61558-1, GB4943-1

LO45-20BxxMU series is one of Mornsun's AC-DC miniaturize open frame power supply and suitable for all kinds of BF type (be accessible to patients) medical system equipment. It features universal AC input and at the same time accepts DC input voltage, cost-effective, high efficiency, high reliability and double or reinforced insulation. These converters offer excellent EMC and safety performance, which meet UL/IEC/EN/ES60601, UL/EN/IEC62368, IEC/EN60335, IEC/EN61558, GB4943 standards and they are widely used in areas of industrial, LED, street light control, electricity, security, telecommunications, smart home, medical, etc.

Selection Guide

Certification	Part No.	Output Power	Nominal Output Voltage and Current (Vo / Io)	Output Voltage Adjustable Range(V)	Efficiency at 230VAC (%) Typ.	Capacitive Load (uF) Max.
CE (pending)	LO45-20B03MU	26.4W	3.3V/8000mA	2.97-3.63	82	20000
	LO45-20B05MU	40W	5V/8000mA	4.5-5.5	84	20000
	LO45-20B12MU	45W	12V/3750mA	10.2-13.8	86	4000
	LO45-20B15MU		15V/3000mA	13.5-18	86	3500
	LO45-20B24MU		24V/1875mA	21.6-28.5	90	1000
	LO45-20B36MU		36V/1250mA	32.4-39.6	90	820
	LO45-20B48MU		48V/940mA	43.2-52.8	90	330

Input Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit
Input Voltage Range	AC input	85	--	264	VAC
	DC input	100	--	370	VDC
Input Frequency		47	--	63	Hz
Input Current	115VAC	--	--	1100	mA
	230VAC	--	--	700	
Inrush Current	115VAC	--	--	40	A
	230VAC	--	--	60	
Leakage Current	240VAC	75uA Max.			
Hot Plug		Unavailable			

Output Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit
Output Voltage Accuracy	0% - 100% load	3.3V/5V output	--	±2	--

		Other output	--	±1	--	
Line Regulation	Rated load	3.3V/5V output	--	±0.8	--	
		Other output	--	±0.5	--	
Load Regulation	230VAC		--	±1	--	
Ripple & Noise*	20MHz bandwidth (peak-to-peak value)	3.3V/5V/12V/ 15V output	--	75	100	mV
		24V output	--	80	120	
		36V/ 48V output	--	100	150	
Stand-by Power Consumption			--	0.2	0.3	W
Temperature Coefficient			--	±0.02	--	%/°C
Short Circuit Protection			Hiccup, continuous, self-recover			
Over-current Protection			≥120%Io, self-recover			
Over-voltage Protection	3.3VDC output		≤5.25V (Output voltage hiccup)			
	5VDC output		≤7V (Output voltage hiccup)			
	12VDC output		≤16V (Output voltage hiccup)			
	15VDC output		≤22V (Output voltage hiccup)			
	24VDC output		≤32.4V (Output voltage hiccup)			
	36VDC output		≤42.4V (Output voltage hiccup)			
	48VDC output		≤57V (Output voltage hiccup)			
Minimum Load			0	--	--	%
Hold-up Time	115VAC input		13	22	--	ms
	230VAC input		65	100	--	

Note: *The "Tip and barrel method" is used for ripple and noise test, 3.3V, 5V, 12V, 15V with a 10uf ceramic capacitor, 24V with a 1uf ceramic capacitor, 48V with a 0.1uf ceramic capacitor, please refer to AC-DC Converter Application Notes for specific information.

General Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit
Isolation	Input-output Electric Strength Test for 1min., leakage current <5mA	4000	--	--	VAC
Insulation Resistance	Input-output 500VDC	≥100x10 ⁹			Ω
Operating Temperature		-40	--	+70	°C
Storage Temperature		-40	--	+70	
Storage Humidity		--	--	90	%RH
Altitude		--	--	5000	m
Power Derating	-40°C to -25°C	1.2	--	--	% / °C
	+50°C to +70°C	2.5	--	--	
	85VAC - 100VAC	1.0	--	--	%/VAC
	2000m-5000m	5.0	--	--	%/Km
Internal	clearance	7.6	--	--	mm
	creepage	8	--	--	
Safety Standard		IEC/EN60601-1 ES60601-1 (3.1 version) CAN/CSA-C22.2 No.60601-1:14-Edition 3 EN60601-1-2 Edition 4 UL/EN/IEC62368-1 EN60335-1 EN61558-1 GB4943-1			
Safety Certification		EN60601/EN62368/EN60335/EN61558 (pending)			
Safety Class		CLASS II			
MTBF		MIL-HDBK-217F@25°C >300,000 h			




Mechanical Specifications

Dimension	76.20 x 50.80 x 26.50 mm
Weight	95g (Typ.)
Cooling method	Free air convection

Electromagnetic Compatibility (EMC)


Emissions	CE	CISPR32/EN55032/EN55011	CLASS B
	RE	CISPR32/EN55032/EN55011	CLASS B
Immunity	ESD	IEC/EN61000-4-2	Contact ±8KV/ Air ±15KV Perf. Criteria A
	RS	IEC/EN61000-4-3	20V/m perf. Criteria A
	EFT	IEC/EN61000-4-4	±2KV perf. Criteria A
	Surge	IEC/EN61000-4-5	Line to line±2KV perf. Criteria A
	CS	IEC/EN61000-4-6	20Vr.m.s perf. Criteria A
	Voltage dips, short interruption and voltage variations	IEC/EN61000-4-11	Dips: >95%; 30%; Interruptions >95%

Product Characteristic Curve




Note: ① With an AC input between 85-100VAC and a DC input between 100-140VDC, the output power must be derated as per temperature derating curves;
② This product is suitable for applications using natural air cooling; for applications in closed environment please consult factory or one of our FAE.


Efficiency Vs Input Voltage (Full Load)



Efficiency Vs Output Load (Vin=230VAC)




Dimensions and Recommended Layout



THIRD ANGLE PROJECTION

Pin-Out			
Connectors	Pin	Mark	Client Connectors
JP1	1	AC(L)	Housing: JST VHR Contact: JSTSVH-21T-P1.1 or equivalent
	2	NoPin	
	3	AC(N)	
JP2	4	-Vo	Housing: JST VHR Contact: JSTSVH-21T-P1.1 or equivalent
	5	-Vo	
	6	+Vo	
	7	+Vo	

Position	Screw Spec.	L(Recommend)	Torque(max)
① - ④	M3	6mm	0.4N·m



- Note:
- For additional information on Product Packaging please refer to www.mornsun-power.com. Packaging bag number: 58220060;
 - Unless otherwise specified, parameters in this datasheet were measured under the conditions of $T_a=25^{\circ}\text{C}$, humidity<75% with nominal input voltage and rated output load;
 - All index testing methods in this datasheet are based on our company corporate standards;
 - We can provide product customization service, please contact our technicians directly for specific information;
 - Products are related to laws and regulations: see "Features" and "EMC";
 - Our products shall be classified according to ISO14001 and related environmental laws and regulations, and shall be handled by qualified units.

Mornsun Guangzhou Science & Technology Co., Ltd.

Address: No. 5, Kehui St. 1, Kehui Development Center, Science Ave., Guangzhou Science City, Huangpu District, Guangzhou, P. R. China
Tel: 86-20-38601850 Fax: 86-20-38601272 E-mail: info@mornsun.cn www.mornsun-power.com